

## Lifting Eye



PLLE4T

Item #	Size (T)	Weight (lbs)	SLL	Safety Factor	UML/T
<b>Lifting Eye</b>					
PLLE1T	1T	2.11	2600	5:1	13000
PLLE2T	2T	3.76	5000	5:1	25000
PLLE4T	4T	8.34	10000	5:1	50000
PLLE8T	8T	20.53	20000	5:1	100000
PLLE20T	20T	41.18	40000	5:1	200000

SLL Safe Lifting Load  
 UML/T Ultimate Mechanical Load in Tension (lbs)

The Lifting Eye is a high strength steel lifting accessory for use with Dog Bone anchors. The Lifting Eye consists of a lifting body and a high strength bail which connects to the Dog Bone anchor. A key feature is the quick connect bail that can rotate freely through 180° degrees under load. Additionally, the spherical head, or lifting eye, has the ability to rotate 360° degrees while under load.

Inspection and maintenance of the Lifting Eye is recommended before each use. The Lifting Eye may experience excessive wear, unexpected damage, bending, twisting, misuse, or overloading during its usable lifetime which can reduce the lifting eye's rating load. Any evidence of wear that exceeds the degree of wear based on its age and typical use suggests that the lifting eye be replaced. Lifting eyes should be used with anchors from the same manufacturer.